



- **Panify: CA3006C41100**

CONTROL and CONNECTIONS

- Personalities: Single mode with 5 control channels
- Control Protocol: DMX, Art-Net, RDM, sACN
- DMX and RDM connectors: Locking 5 pin XLR IN/THRU
- Ethernet port: RJ45 IN
- Power connector: PowerCon True1 IN/OUT
- Built In Web Server

DYNAMIC EFFECTS

- Pan Endless
- Max applicable weight: 30Kg (with the weight of the fixture balanced on the Panify)
- Max rotation speed: 43RPM

HARDWARE and SOFTWARE

- Long life self-charging battery
- Display Graphic LCD backlit b/w Display
- Firmware upload from another fixture
- Firmware Upgrade via Web Server
- Diagnostic
- DMX monitoring
- Remote access through RDM
- CloudIO compatibility

HOUSING

- Aluminum and steel structure with plastic covers
- Two side handles for transportation
- IP66 protection rate

WORKING POSITION

- Working in any position
- Hanging system: with fast-lock omega clamps (1/4 turn) on the base

ELECTRICAL

Operating Voltage: 100-240V, 50/60 Hz

- Power Supply: Electronic auto range with active PFC
- Max Power consumption: 220VA
- Mains Out: 2300 VA @ 230V; 1250 VA @ 110V

THERMAL SPECIFICATION

- Max ambient temperature 45°C (113°F)
- Min ambient temperature -20°C (-4°F)

SAFETY SPECS

- Fuse 4A – 250V
- Forced ventilation with axial fans

COMPLIANCE

- CE: conforms to the European Directives
- UKCA: conforms to UK Regulations
- EAC: conforms to EurAseC Regulations
- cMETus Listed

PACKAGING

- Carton box + Polystyrene
- Flight case + Foam shell (4 position)
- Distance between two fixtures: Depending from installed product.

WEIGHT - SIZE

- 13.8 Kg (30.4 lbs)
- 390.8mm x 295mm x 252.8mm

ACCESSORIES

- ETL Mains cable, 1.5mt. (Bare Ends / IP65 PowerConTrue1 connector): CAB02B-802 (included)
- Omega bracket: 2x 183102/805 (included)
- Power cables 0.5mt.: 1x CAB0PR/801 (included)
- DMX cable 0.5mt.: CAB0PS/801 (included)
- Safety chains 0.5mt.: 2x FUN00C/001 (included)
- Screws/Bolts/Washers: 4x418100-801 (included)

- Clamp: C21070 (optional)
- Safety chain: 105041-003 (optional)
- Power Con True1 connector: CON000 (optional)
- Foam shell: F21329/001 (optional)
- Flight case 4 pos.: CF1016 (optional)
- Universal bracket: CA3017000102 (optional)